



INSTALLATION NOTES:

1. SILT FENCE SHOULD BE A MINIMUM OF 5 FEET FROM THE TOE OF SLOPE.
2. FILTER CLOTH SHALL BE FASTENED SECURELY TO THE CHAIN LINK FENCE WITH TIES SPACED EVERY 24 INCHES HORIZONTALLY AT THE TOP AND MIDDLE (VERTICAL) SECTIONS.
3. WHEN TWO HORIZONTAL SECTIONS OF FILTER FABRIC ADJOIN EACH OTHER, THEY SHALL BE OVERLAPPED BY 6 INCHES AND FOLDED.

MAINTENANCE NOTES:

1. MEASURES SHALL BE INSPECTED AT LEAST ONCE A WEEK OR IMMEDIATELY AFTER EACH RAINFALL OF 1.0 INCH OR GREATER.
2. FABRIC SHALL BE REPLACED PROMPTLY IF FOUND TO BE IN DISREPAIR.
3. ACCUMULATED SEDIMENT SHALL BE REMOVED AFTER EACH STORM EVENT AND WHEN IT REACHES APPROXIMATELY 1/3 OF THE HEIGHT OF THE CHAIN-LINK FENCE.

CITY OF RALEIGH STANDARD DETAIL		
REVISIONS	DATE: 9/2024	NOT TO SCALE
	SUPER SILT FENCE	
	SW-20.03	