



INSTALLATION NOTES:

1. PROVIDE DRAINAGE AWAY FROM THE WASH RACK TO AN APPROVED SEDIMENT TRAPPING DEVICE.
2. THE WASH RACK LOCATION MUST SLOPE AWAY FROM THE STREET OR STEPS MUST BE TAKEN (GRADING, DIVERSIONS, ETC.) TO PREVENT RUNOFF FROM FLOWING INTO THE STREET.
3. IT IS ADVISABLE TO PROVIDE A SEPARATE STABILIZED CONSTRUCTION ENTRANCE FOR SMALLER VEHICLES TO ACCESS THE SITE TO LIMIT TRAFFIC ACROSS THE RACK AND REDUCE WEAR AND MAINTENANCE.

MAINTENANCE NOTES:

1. MEASURES SHALL BE INSPECTED AT LEAST ONCE A WEEK OR IMMEDIATELY AFTER EACH RAINFALL OF 1.0 INCH OR GREATER. MAKE ANY REQUIRED REPAIRS IMMEDIATELY.
2. MAINTAIN AS NEEDED TO PREVENT MUD OR SEDIMENT FROM LEAVING THE CONSTRUCTION SITE.
3. IMMEDIATELY REMOVE ALL MATERIALS SPILLED, WASHED, OR TRACKED ONTO PUBLIC ROADWAYS.

**THIS IS AN EXAMPLE OF AN ACCEPTABLE WASH RACK. OTHER APPROVED METHODS MAY BE UTILIZED.

CITY OF RALEIGH		
STANDARD DETAIL		
<i>REVISIONS</i>	<i>DATE: 9/2024</i>	<i>NOT TO SCALE</i>
	CONSTRUCTION EXIT WASH RACK	
	SW-20.14	