



IF THE FINAL LIFT OF ASPHALT HAS BEEN INSTALLED AND IS DAMAGED DURING CURB REMOVAL, A ONE FOOT WIDE SECTION OF ASPHALT SHOULD BE SAWCUT AND REMOVED FOR FORMS TO BE USED TO KEEP A STRAIGHT EDGE ON THE DRIVEWAY APRON. REINSTALL HOT MIX SURFACE ASPHALT PATCH S9.5B.

IF THE FINAL LIFT OF ASPHALT HAS NOT BEEN INSTALLED, THE ASPHALT IN FRONT OF THE APRON CAN REMAIN IN PLACE.

NOTES:

1. CURB AND GUTTER SECTION SHALL BE REMOVED IN ACCORDANCE WITH DRIVEWAY WIDTH APPROVED BY THE CITY.
2. IF PERPENDICULAR CUT IS LESS THAN 5' FROM NEXT JOINT, THEN THE PARALLEL CUT SHALL BE MADE TO THAT JOINT.
3. THIS METHOD IS NOT ALLOWED IN NEW ROADWAY CONSTRUCTION.

| CITY OF RALEIGH | | |
|------------------------|---|--------------|
| STANDARD DETAIL | | |
| REVISIONS | DATE: 8/2020 | NOT TO SCALE |
| | STANDARD METHOD OF REMOVING EXISTING CURB (FOR A DRIVEWAY APRON INSTALLATION) | |
| | | |
| | | |
| | | |
| | | |
| T-10.24 | | |